

SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT I, YASUHIKO INAGAKI, a citizen of Japan residing at Atsugi-Shi, Kanagawa, Japan have invented certain new and useful improvements in

SIGNAL OUTPUT CIRCUIT

of which the following is a specification:-

TITLE OF THE INVENTION

SIGNAL OUTPUT CIRCUIT

BACKGROUND OF THE INVENTION

5 1. Field of the Invention

The present invention relates generally to signal output circuits, and more particularly to a signal output circuit having the function of shutting down the operation of an internal circuit (a shutdown function) and
10 the function of muting a signal (a mute function).

2. Description of the Related Art

A conventional audio amplifier circuit that amplifies an audio signal and outputs the audio signal to headphones or a speaker is known.

15 Such an audio amplifier circuit has a shutdown function and a mute function for cutting noise at the time of turning on or turning off power.

FIG. 1 is a block diagram showing a conventional audio amplifier circuit 101.

20 An input signal is supplied from a signal source 102 to the input terminal T_{in} of the audio amplifier circuit 101 via a capacitor C41 for cutting a direct current. The input signal supplied to the input terminal T_{in} is supplied to an amplifier circuit 111. The amplifier
25 circuit 111 includes a differential amplifier circuit 121, an input resistor R31, a feedback resistor R32, and a switch 122, and has a reference voltage applied thereto from a reference voltage generator circuit 112, thus forming an inverting amplifier circuit.

30 The amplifier circuit 111 outputs a signal that is a function of the difference between the reference voltage from the reference voltage generator circuit 112 and the input signal supplied to the input terminal T_{in} .

The signal amplified by the amplifier circuit 111 is output from an output terminal T_{out} to drive a speaker 103.

The switch 122 is provided between the connection point of the input resistor R31 and the feedback resistor R32 and the inverting input terminal of the differential amplifier circuit 121. The switch 122 is switched in accordance with a mute signal supplied from a controller 104 to a control terminal T_{cnt1} . When the level of the mute signal is HIGH, the switch 122 short-circuits the connection point of the input resistor R31 and the feedback resistor R32 and the inverting input terminal of the differential amplifier circuit 121 so that the input signal is inverted and amplified to be output from the output terminal T_{out} .

When the level of the mute signal is LOW, the switch 122 short-circuits the output of the differential amplifier circuit 121 and its inverting input terminal, thereby causing a mute state so as to prevent the input signal from being output from the output terminal T_{out} . Thus, the switch 122 is switched in accordance with the mute signal supplied from the controller 104 to the control terminal T_{cnt1} , so that the supply of the input signal to the differential amplifier circuit 121 is controlled. As a result, the mute function is controlled.

The reference voltage generator circuit 112 includes a switch 131, resistors R41 and R42, and a capacitor C51. A constant voltage V_{dd} is applied to the reference voltage generator circuit 112. The constant voltage V_{dd} is applied via the switch 131 to a series circuit formed of the resistors R41 and R42. When the level of a shutdown signal supplied from the controller 104 to a control terminal T_{cnt2} is HIGH, the switch 131 is turned ON to apply the constant voltage V_{dd} to the series

circuit formed of the resistors R41 and R42. When the level of the shutdown signal is LOW, the switch 131 is turned OFF to stop the applying of the constant voltage V_{dd} to the series circuit formed of the resistors R41 and R42.

5 When the switch 131 is ON, the resistors R41 and R42 divide the constant voltage V_{dd} to generate the reference voltage. The generated reference voltage is supplied to the non-inverting input terminal of the differential amplifier circuit 121. As a result, the
10 amplifier circuit 111 is put in an operating state. A terminal T_c is connected to the connection point of the resistors R41 and R42, and an external capacitor C51 is connected to the terminal T_c . The capacitor C51 connected to the terminal T_c absorbs the ripple of the reference
15 voltage to stabilize the reference voltage.

Next, a description is given of the operation of the audio amplifier circuit 101.

FIG. 2 is a diagram for illustrating the operation of the audio amplifier circuit 101. In FIG. 2,
20 (a) indicates the shutdown signal output from the controller 104, (b) indicates the switching of the switch 131, (c) indicates the reference voltage supplied to the differential amplifier circuit 121, (d) indicates the mute signal output from the controller 104, and (e) indicates
25 the switching of the switch 122.

Referring to FIG. 2, when the level of the shutdown signal switches from LOW to HIGH at a time t_{10} as shown in (a), the switch 131 is switched from OFF state to ON state as shown in (b). As a result of the switching of
30 the switch 131 to ON state, the reference voltage is generated by the resistors R41 and R42. At this point, as shown in (c), the reference voltage is caused by the external capacitor C51 to gradually rise to reach a

predetermined level at a time t11. When the reference voltage reaches the predetermined level at the time t11, the differential amplifier circuit 121 is released from a shutdown state to enter an operating state.

5 The controller 104 counts a predetermined period of time since the time t10, when the level of the shutdown signal switches to HIGH. The controller 104 outputs the mute signal at a time t12, when the preset predetermined period of time passes, as shown in (d) of FIG. 2. The
10 mute signal turns ON the switch 122 of the amplifier circuit 111 as shown in (e) of FIG. 2. As a result, the input signal is released from a mute state, and is amplified by the amplifier circuit 111 to be supplied to the speaker 103.

15 Thus, according to the conventional audio amplifier circuit 101, the generation of the reference voltage in the reference voltage generator circuit 112 is controlled based on the shutdown signal supplied from the controller 104. As a result, the operation of the
20 amplifier circuit 111 is controlled, and thus, the shutdown function is controlled. Further, the mute function of the amplifier circuit 111 is controlled based on the mute signal supplied from the controller 104.

 According to the conventional audio amplifier
25 circuit, the shutdown signal and the mute signal should be input separately to an integrated circuit. This increases the number of external pins of the integrated circuit, thus making it difficult to reduce the size of the integrated circuit.

30 Therefore, in order to reduce the number of external pins, an audio amplifier circuit that controls both the shutdown function and the mute function in accordance with the level of the shutdown signal has been

proposed (United States Patent No. 5,642,074).

According to the conventional audio amplifier circuit where the shutdown signal for controlling the shutdown function and the mute signal for controlling the mute function are separately supplied from an external controller and control the shutdown function and the mute function, respectively, it is necessary to generate the shutdown signal and the mute signal in the external controller, and it is necessary to control timing for generating these signals. This causes a problem in that a load is imposed on the processing of the controller.

According to the conventional audio amplifier circuit controlling both of the shutdown function and the mute function in accordance with the level of the shutdown signal, timing for controlling the shutdown function and timing for controlling the mute function cannot be determined with accuracy, so that in some cases, noise may be output when an amplifier is activated.

20 SUMMARY OF THE INVENTION

Accordingly, it is a general object of the present invention to provide a signal output circuit in which the above-described disadvantages are eliminated.

A more specific object of the present invention is to provide a signal output circuit that can control timing for canceling a shutdown function and timing for canceling a mute function at different times with accuracy using a single external control signal.

The above objects of the present invention are achieved by a signal output circuit for controlling output of an input signal, including: an internal circuit; a digital delay circuit delaying by digital processing a control signal for controlling an operation of the

internal circuit; and a switch muting the input signal in accordance with a delayed output of the digital delay circuit.

According to the above-described signal output circuit, the muting of an input signal is performed by delaying a control signal controlling the operation of the internal circuit, such as a shutdown signal, by digital processing. Accordingly, there is no need to supply a mute signal separately from the control signal, so that the number of external terminals can be reduced. As a result, the chip size of an integrated circuit can be reduced.

Further, a delay period of time for which the control signal is delayed by the digital delay circuit is set so that the muting of the input signal is canceled after the internal circuit is activated by the control signal. Accordingly, the muting of the input signal can be canceled after it is ensured that the internal circuit is activated. Further, the delay period of time can be set with accuracy by digital processing by the digital delay circuit. Accordingly, it is possible to prevent noise from being output when power is turned on.

BRIEF DESCRIPTION OF THE DRAWINGS

Other objects, features and advantages of the present invention will become more apparent from the following detailed description when read in conjunction with the accompanying drawings, in which:

FIG. 1 is a block diagram showing a conventional audio amplifier circuit;

FIG. 2 is a diagram for illustrating the operation of the conventional audio amplifier circuit;

FIG. 3 is a block diagram showing an audio

amplifier circuit according to an embodiment of the present invention;

FIG. 4 is a block diagram showing a delay circuit of the audio amplifier circuit according to the embodiment of the present invention; and

FIG. 5 is a diagram for illustrating the operation of the audio amplifier circuit according to the embodiment of the present invention.

10 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

A description is given below, with reference to the accompanying drawings, of an embodiment of the present invention.

FIG. 3 is a block diagram showing an audio amplifier circuit 1 according to the embodiment of the present invention.

The audio amplifier circuit 1 is composed of a single-chip semiconductor integrated circuit including amplifier circuits 11 and 12 and a function control circuit 13. The audio amplifier circuit 1 includes an input terminal T_{in} , an inverting output terminal T_{out-} , a non-inverting output terminal T_{out+} , a shutdown control terminal T_{sd} , and a terminal T_c as external terminals. An input signal is supplied from a signal source 2 to the input terminal T_{in} via a capacitor C1. A shutdown signal is supplied from a controller 4 to the shutdown control terminal T_{sd} . A speaker 3 is connected between the inverting and non-inverting output terminals T_{out-} and T_{out+} . A capacitor C2 is connected to the terminal T_c .

30 The input signal supplied to the input terminal T_{in} is supplied to the amplifier circuit 11. The amplifier circuit 11 includes an input resistor R1, a feedback resistor R2, a differential amplifier circuit 21, and a

switch circuit 22, forming an inverting amplifier circuit. The amplifier circuit 11 inverts, amplifies, and outputs the input signal supplied to the input terminal T_{in} .

5 The switch circuit 22 is a circuit for realizing a mute function. The switch circuit 22 is connected between the connection point of the resistors R1 and R2 and the inverting input terminal of the differential amplifier circuit 21. The switch circuit 22 is turned ON when the level of a mute signal supplied from the function
10 control circuit 13 is LOW, and is turned OFF when the level of the mute signal is HIGH. When the switch circuit 22 is turned ON, the switch circuit 22 short-circuits the connection point of the resistors R1 and R2 and the inverting input terminal of the differential amplifier
15 circuit 21 so that the input signal is supplied to the inverting input terminal of the differential amplifier circuit 21. As a result, the muting of the input signal is canceled so that the amplifier circuit 11 inverts and amplifies the input signal.

20 When the switch circuit 22 is turned OFF, the switch circuit 22 disconnects the connection point of the resistors R1 and R2 and the inverting input terminal of the differential amplifier circuit 21, and short-circuits the output terminal and the inverting input terminal of
25 the differential amplifier circuit 21. As a result, the amplifier circuit 11 mutes the input signal.

The output signal of the amplifier circuit 11 is output from the inverting output terminal T_{out-} , and is also supplied to the amplifier circuit 12.

30 The amplifier circuit 12 includes an input resistor R11, a feedback resistor R12, a differential amplifier circuit 31, and a switch circuit 32, forming an inverting amplifier circuit. The amplifier circuit 12

inverts and amplifies the signal supplied from the amplifier circuit 11, and outputs the signal from the non-inverting output terminal T_{out+} .

The switch circuit 32 is a circuit for realizing the mute function. The switch circuit 32 is connected between the connection point of the resistors R11 and R12 and the inverting input terminal of the differential amplifier circuit 31. The switch circuit 32 is turned ON when the level of the mute signal supplied from the function control circuit 13 is LOW, and is turned OFF when the level of the mute signal is HIGH. When the switch circuit 32 is turned ON, the switch circuit 32 short-circuits the connection point of the resistors R11 and R12 and the inverting input terminal of the differential amplifier circuit 31 so that the input signal is supplied to the inverting input terminal of the differential amplifier circuit 31. As a result, the muting of the input signal is canceled so that the amplifier circuit 12 inverts and amplifies the input signal.

When the switch circuit 32 is turned OFF, the switch circuit 32 disconnects the connection point of the resistors R11 and R12 from the inverting input terminal of the differential amplifier circuit 31, and short-circuits the output terminal and the inverting input terminal of the differential amplifier circuit 31. As a result, the amplifier circuit 12 mutes the input signal.

The output signal of the amplifier circuit 12 is output from the non-inverting output terminal T_{out+} .

The shutdown signal is supplied from the controller 4 to the shutdown control terminal T_{sd} . For instance, the controller 4 inverts the level of the shutdown signal from LOW to HIGH when power is turned on. The shutdown signal output from the controller 4 is

supplied to the function control circuit 13.

The function control circuit 13 includes a reference voltage generator circuit 41 and a delay circuit 42. The reference voltage generator circuit 41 is a
5 circuit for realizing a shutdown function, and includes a switch 51, resistors R21 through R24, and a bypass circuit 52. An external capacitor C2 is connected to the terminal T_c of the reference voltage generator circuit 41.

The switch 51 is turned ON when the level of the
10 shutdown signal is HIGH, and is turned OFF when the level of the shutdown signal is LOW. When the switch 51 is turned ON, a constant voltage V_{dd} is applied to a series circuit formed of the resistors R21 and R22. The constant voltage V_{dd} is divided between the resistors R21 and R22,
15 and a divided voltage is output from the connection point of the resistors R21 and R22.

The connection point of the resistors R21 and R22 is connected via a series circuit formed of the resistors R23 and R24 to the non-inverting input terminal
20 of the differential amplifier circuit 21 of the amplifier circuit 11 and the non-inverting input terminal of the differential amplifier circuit 31 of the amplifier circuit 12. The connection point of the resistor R24 and the non-inverting input terminals of the differential amplifier
25 circuits 21 and 31 is connected to the terminal T_c .

The capacitor C2 is connected to the terminal T_c . The capacitor C2 absorbs variations in a (reference) voltage applied to the non-inverting input terminals of the differential amplifier circuits 21 and 31.

30 The bypass circuit 52 bypasses the resistor 24 when the switch 51 is turned ON. Without the bypass circuit 52, when the switch 51 is turned ON, the voltage applied to the non-inverting input terminals of the

differential amplifier circuits 21 and 31 would rise with a delay of a time constant determined by the resistors R23 and R24 and the capacitor C2. Accordingly, in order to reduce the delay and activate the amplifier circuits 11 and 12 quickly, the bypass circuit 52 is provided.

The bypass circuit 52 includes CMOS (complementary metal oxide semiconductor) FETs (field effect transistors) Q1 and Q2 and an inverter 61, thus forming a transfer gate forming a transmission path bypassing the resistor R24. The output of the delay circuit 42 is applied to the gates of the MOS FETs Q1 and Q2. The MOS FETs Q1 and Q2 are switched ON when the level of the output of the delay circuit 42 becomes LOW, and are switched OFF when the output of the delay circuit 42 is delayed for a predetermined period of time so that the level thereof is switched to HIGH.

Accordingly, when the shutdown signal is supplied to turn the switch 51 ON, the bypass circuit 52 bypasses the resistor R24. As a result, the resistance is reduced. This increases a charging current for the capacitor C2 connected to the terminal T_c so that the capacitor C2 is charged at high speed. Accordingly, the voltage applied to the non-inverting input terminals of the differential amplifier circuits 21 and 31 rises quickly, thus making it possible to cause the amplifier circuits 11 and 12 to operate early.

The delay circuit 42 is a circuit for controlling the mute signal. The delay circuit 42 delays the shutdown signal for a predetermined period of time and outputs the delayed shutdown signal as the mute signal. The predetermined period of time is set to a period of time required before it is ensured that the amplifier circuits 11 and 12 operate after the amplifier circuits 11

and 12 are activated based on the shutdown signal.

FIG. 4 is a block diagram showing the delay circuit 42.

The delay circuit 42 includes an oscillator
5 circuit (OSC) 71, an inverter 72, and flip-flops 73-1
through 73- n , thus forming a logic timer.

When the level of the shutdown signal supplied
to the shutdown control terminal T_{sd} switches from LOW to
HIGH, the oscillator circuit 71 starts to oscillate, and
10 supplies the oscillation output to the inverter 72 and the
flip-flop 73-1. The inverter 72 inverts and outputs the
oscillation output of the oscillator circuit 71.

The flip-flops 73-1 through 73- n are formed of
D-type flip-flops. The shutdown signal is supplied to the
15 reset terminal R of each of the flip-flops 73-1 through
73- n so that the level of an output Q is reset to LOW by
the shutdown signal. In the flip-flop 73-1, the
oscillation output of the oscillator circuit 71 is
supplied to a clock terminal C, the oscillation output
20 inverted by the inverter 72 is supplied to the inverting
clock terminal NC, and an inverting output terminal NQ is
connected to a data terminal D. Further, the inverting
output terminal NQ and a non-inverting output terminal Q
are connected to the clock terminal C and the inverting
25 clock terminal NC, respectively, of the flip-flop 73-2 at
the next stage.

Such connection between the flip-flops 73-1 and
73-2 is performed on the n flip-flops 73-1 through 73- n .
As a result, a so-called "up counter" is formed. The
30 level of the output of the non-inverting output terminal Q
of the flip-flop 73- n at the last stage rises to HIGH
after counting the oscillation output of the oscillator
circuit 71 2^n times. As a result, the delayed shutdown

signal is output.

Thus, the delay circuit 42 forms a logic timer, and provides delay by digital processing. Accordingly, a delay period can be set with accuracy compared with the case of using a capacitor.

According to this embodiment, the delay circuit 42 is formed of a logic timer. The delay circuit 42, however, is not limited to this, and may employ any configuration that can set a delay period by digital processing.

Next, a description is given of an operation of the audio amplifier circuit 1 according to this embodiment.

FIG. 5 is a diagram for illustrating the operation of the audio amplifier circuit 1 according to this embodiment. In FIG. 5, (a) indicates the shutdown signal supplied from the controller 4 to the shutdown control terminal T_{sd} , (b) indicates the switching of the switch 51, (c) indicates the reference voltage applied to the non-inverting input terminals of the differential amplifier circuits 21 and 31, (d) indicates the output of the delay circuit 42, and (e) indicates the switching of the switch circuit 22 and 32.

Referring to FIG. 5, when the level of the shutdown signal switches from LOW to HIGH at a time t_0 as shown in (a), the switch 51 is turned ON as shown in (b). At this point, the bypass circuit 52 is in the ON state. As a result, the external capacitor 2 is rapidly charged so that the reference voltage (of a predetermined level) is applied to the non-inverting input terminals of the differential amplifier circuits 21 and 31 at a time t_1 as shown in (c).

Thereafter, at a time t_2 ($> t_1$), when a predetermined delay period of time ΔT passes since the

time t_0 , the level of the output of the delay circuit 42 rises to HIGH as shown in (d), and the switch circuits 22 and 32 are turned ON as shown in (e). The switch circuits 22 and 32 are turned ON to cancel the muting of the input
5 signal so that the input signal is amplified by the amplifier circuits 11 and 12 to be supplied to the speaker 3.

According to the audio amplifier circuit 1 of this embodiment, by only supplying the shutdown signal
10 from the shutdown control terminal T_{sd} , a mute state (the muting of the input signal) can be canceled after a shutdown state (the shutdown of the internal circuit of the audio amplifier circuit 1) is canceled. That is, muting is performed by delaying the shutdown signal
15 (control signal) by digital processing. Accordingly, there is no need to supply a mute signal separately from the shutdown signal from the controller 4. Therefore, the number of external terminals of the audio amplifier circuit 1 can be reduced. As a result, the chip size of
20 the integrated circuit can be reduced. Further, the controller 4 may generate only the shutdown signal. Accordingly, the processing load on the controller 4 can be reduced.

Further, by generating the mute signal
25 controlling the mute state by delaying the shutdown signal, the mute state can be canceled after the shutdown state is canceled. Accordingly, the input signal can be muted before activating the differential amplifier circuits 21 and 31. As a result, a great variation in output at the
30 time of activating the differential amplifier circuits 21 and 31 can be prevented so that the amplifier circuits 21 and 31 can be activated smoothly.

That is, according to the present invention, the

delay period of time ΔT is set so that the muting of the input signal is canceled after the differential amplifier circuits 21 and 31 are activated by the shutdown signal. Accordingly, the muting of the input signal can be

5 canceled after it is ensured that the differential amplifier circuits 21 and 31 are activated. Further, the delay period of time ΔT can be set with accuracy by digital processing by the digital delay circuit 42. Accordingly, it is possible to prevent noise from being

10 output when power is turned on.

The present invention is not limited to the specifically disclosed embodiment, and variations and modifications may be made without departing from the scope of the present invention.

15 The present application is based on Japanese priority patent application No. 2003-282847, filed on July 30, 2003, the entire contents of which are hereby incorporated by reference.